



## M2S 660-11-K-Y

- Rubber enclosure
- soldering terminals and spade terminals
- Metal coating

## Data

### Ordering data

Product type description	M2S 660-11-K-Y
Article number (order number)	101055373
EAN (European Article Number)	4030661005157
eCl@ss number, version 12.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 9.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

### Approvals - Standards

Certificates	EAC
--------------	-----

### General data

Standards	EN IEC 60947-5-1
Material of the contacts, electrical	Gold-plated silver (AgNi 0,15 + Au 0,3µm)
Gross weight	112 g

## General data - Features

Number of normally closed (NC)	1
Number of normally open (NO)	1

## Mechanical data

Mechanical life, minimum	3,000,000 Operations
Actuating speed, minimum	1 mm/min

## Mechanical data - Connection technique

Terminal designations	H05VV-F
Wire cross-section	0.75 mm <sup>2</sup>

## Ambient conditions

Degree of protection	IP65
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

## Ambient conditions - Insulation values

Rated insulation voltage $U_i$	250 V
Rated impulse withstand voltage $U_{imp}$	4 kV

## Electrical data

Thermal test current	4 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	1 A
Switching principle	Snap action with self-cleaning contact
Switching frequency	30,000 /h

## Pictures

## Product picture (catalogue individual photo)




ID: KM660F05

| 326.3 kB | .jpg | 222.956 x 340.431 mm - 632 x 965 px - 72 dpi

| 51.3 kB | .png | 74.083 x 112.889 mm - 210 x 320 px - 72 dpi

## Dimensional drawing basic component



ID: Km660g02

| 123.5 kB | .jpg | 352.778 x 236.714 mm - 1000 x 671 px - 72 dpi

Schmersal Ltd., Sparrowhawk Close, WR14 1GL Malvern

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 28/11/2022, 08:07